#### MATERIAL SAFETY DATA SHEET

DATE: 06/29/99

Revision #1 Page # of 2

For Chemical Emergency Only:

(800) 424-9300 In the US & Canada:

Int'l & Wash DC (COLLECT): (202) 483-7616

Telephone for Information: (909) 987-0550

# Rancho Cucamonga, CA 91730 PRODUCT IDENTIFICATION:

HAZARD RATING

C070 Lanco Contact Cement

Section 1

PACER TECHNOLOGY

9420 Santa Anita Avenue

1 x 0

## Section 2 - HAZARDOUS INGREDIENTS INFORMATION:

Hazardous Component	ts	OSHA	ACGIH	OTHER	%
(Common Names, CAS Number)		PEL	TLV	LIMITS	OPTION
Methyl Ethyl Ketone*	(78 <del>-93-3</del> )	200ppm	200ppm		15-35
n-Hexane*	(110-54-3)	50ppm	50ppm		1 <b>5-3</b> 5
Ethyl Acetate	(141-78-6)	400ppm	400ppm		15-35

<sup>\*</sup> This ingredient is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

# Section 3 - PHÝSICAL/CHEMICAL CHARACTERISTICS:

0.849Specific Gravity (H2O=1): Bolling Point: 156 - 189 F Vapor Density (Air=1): >1 Meltina Point: NE Vapor Pressure (mm Hg): 124 Evaporation Rate (Butyl acetate = 1): >1

Solubility in Water: 9,5% soluble.

Appearance & Odor: Clear liquid with an ester type odor.

### Section 4 • FIRE AND EXPLOSION HAZARD DATA:

Flash Point (Method): 10 F (TCC) Flammable Limits: LEL: 1.10% UEL: 11.50%

Extinguishing Media: Dry chemical, foam or carbon dioxide.

Special Fire Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water may be unsultable as an extinguishing medium, but is helpful in keeping adjacent containers cool. Juusual Fire and Explosion Hazards: Keep away from heat, sparks, open flames. Vapors can cause a flash fire. Vapors might also ignite explosively.

# Section 5 - REACTIVITY DATA:

Stability: Unstable \_\_ Stable XX Conditions to Avoid: Heat, sparks or flame.

ncompatibility (Materials to Avoid): Acids, alkaline materials, amines, strong oxidizing agents.

lazardous Decomposition Products: Carbon dioxide, carbon monoxide.

fazardous Polymerization: May Occur May Not Occur XX

### Section 6 - HEALTH HAZARD DATA:

Route(s) of Entry: Inhalation: Yes Skin: Yes Ingestion: Yes

Health Hazards (Acute and Chronic):

Acute - Temporary dizziness, headache, possible nausea by inhalation. Solvents may defat skin if contact occurs.

Chronic - Prolonged or repeated skin contact may cause dermatitis in sensitive individuals.

Carcinogenicity: NTP: No IARC Monographs: No OSHA Regulated: No

### First Aid Procedures:

Eye contact - Immediately flush eye with copious amounts of water for 15 minutes. Contact physician.

Skin contact - Irritation upon direct contact. Remove contaminated clothing and wash affected areas with soap and water. Prolonged or repeated contact can cause dermatitis in sensitive Individuals.

Inhalation - Remove to fresh air. Perform artificial respiration if breathing has stopped.

Ingestion - Do not induce vomiting. Get immediate medical attention.

Medical Conditions Generally Aggravated by Exposure: Pre-existing skin and respiratory conditions.

#### Section 7 - PRECAUTIONS FOR SAFE HANDLING AND USE:

Steps to Be Taken in Case Material is Released or Spilled: Remove source of lightion and provide ventilation. Soak up with inert absorbent. Large spills may be scooped up with non-sparking tools. Place into container for disposal.

Waste Disposal Method: Dispose of in accordance with local, state, and federal EPA regulations.

**Precautions to Be Taken in Handling and Storing:** Store in a cool location away from heat, spacks or flames. Do not breathe spray mist. Spray mist and vapors are flammable.

Other Precautions: Ground container when transferring product. Do not cut, puncture, or weld on or near empty container.

### Section 8 - CONTROL MEASURES:

Respiratory Protection (Specify Type): A NIOSH approved vapor canister may be used to maintain vapor concentration below TLV.

/entilation: Local Exhaust: To maintain vapor concentration below TLV.

Mechanical (General): As needed.

Protective Clothing or Equipment: Safety glasses/goggles with side shields, rubber gloves and aprono protect skin and clothing.

Nork/Hyglenic Practices: Wash hands with soap and water after use. Launder contaminated clothing perfore reuse.

NE = Not established

The data contained herein is based upon information that Pacer Technology believes to be reliable. Users of this product ave the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and rotaction of property and persons involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the esuits to be obtained from the use thereof.